




## Recessed 4.75" 25Watt Light Engine



**CREE**



### Features

- Is a 25watt Triac Dimmable LED light engine
- Dimming with most TRIAC or SRC dimmers, dims 0-100%
- 25 watt units available
- 12 high intensity white color Cree emitters
- Available in 3000K, 4000K, 5000K, 6500K whites and solid colors
- Provides upto 1680 usable lumens in 6500K white
- Lumen maintenance 50,000+ L70 @ 50°C (full output)
- Lens options 10° standard, 5,10,20,39,44x11 available
- Highest color / flux binning
- CRI of 82+
- For use in Dry locations (IP20)
- Features built in over voltage and over current protection
- Cannot see the light source with LSD
- Light Engine is DESIGNED & MANUFACTURED IN THE U.S.A

### Control

- Dimmable via conventional dimming (Triac)
- Dims from 100 to 0%

### Cooling

- Proprietary patent pending heat management system, based around a substantial heatsink construction and patented carbon foam heat distribution, silent running - no fans

### Construction

- Extremely robust housing suitable for touring, permanent and temporary applications
- Driver is encapsulated.

### Mounting

- This Engine can have custom panel work made to suit most housings larger than 4.5"

### Finish

- Power Coated Black as standard (other colors to order at an additional cost)

### Weight & Dimensions

- With yoke 4lbs (1.82kg)
- 7.2" (182mm) length x 7.2" (182mm) width x 13.5" (342mm) height

### Electrical

- 110 or 220-277VAC Drivers available

### Power Consumption

- Low power consumption (24 watts at full intensity) virtually no heat generated
- No fans, silent running

### Certifications

- Certifications – ETL & CE (Pending early 2012)
- Environment - Dry & Damp locations

### Warranty

- 3 year limited warranty, extended warranty available



**PARLIGHTS, INC.**  
Theatrical Lighting & Rigging

One Wormans Mill Court, # 7  
Frederick, MD 21701  
www.parlights.com

301.698.9242  
fax 301.846.0369  
sales@parlights.com